

## Fire-rated Handle

This lever handle is applicable on fire-rated door. The fire-rated period is 3 hours. Not only conforms to EN1634, but this lever also confirms to EN1906 and DIN18251.

Material: Stainless Finish/Color: Satin Finish Durability Testing: 200,000 times Fire-rated Testing period: 3 hours Specification: EN1906, DIN18251

Fire-rated Handle

Allenwrench 1pcs

1 110 10100 110110110		
Product No.	Model No.	
500030	LH8101	
500031	LH8103	
Parts included:		
Fire-rated Handle	e 1pair	
Escutcheon 1pcs		
Assembly screws	1set	



## Standard Cylinder

This is a 6 pins-tumbler locking cylinder made of brass and the bottom pin is made of stainless steel.

Material: Brass, Stainless Finish/Color: Satin Nickel Durability Testing: 200,000 times Specification: EN1303:2005

Standard Cylinder Product No. 500046

Parts included: Standard Cylinder 1pcs Brass key 5pcs

Steel screw 1pcs






Material: (Escutcheon) Stainless ⟨Base⟩Steel Finish/Color: Satin Finish

Euro Profile escutcheon
Product No.
500045
Parts included:

Euro Profile escutcheon 1set







35

70


35





H L 8101

140











## Rectangular Flush Cover

This product is useful to cover cylinder lock so the door looks seamless. Pull the cover up to operate the cylinder.


Material: Stainless


Rectangular Recessed Pull				
Product No.	Finish/Color			
500040	Satin Finish			
500041	Black			

Screw included:

4 × 12 Flat head machine screw(D7) 4pcs Parts included:

Rectangular Recessed Pull 1pcs Assembly screws 1set











## **Euro Fire-rated Hinge**


This hinge is applicable on fire-rated door with a fire-rated period for 2 hours. This product not only conforms to EN1634, but it also confirms to EN1935:2002 Grade 13.

Material: Stainless Finish/Color: Raw Material

Euro fire-rated hinge		
Product No.	Size(mm)	Material
500000	127×76×t3	SUS304
500001	$102 \times 76 \times t3$	SUS304
500002		SUS316
500003	$127 \times 89 \times t3$	SUS304
500004		SUS316
Carou includo	۷٠	

Screw included:  $4.5 \times 30$  Flat head tapping screw 8pcs Parts included:

Euro fire-rated hinge 1pcs Assembly screws 1set



The number of hinges required Door height (mm) Hinges Quantity Below 1523 1524~2285 3 2286~3048 4

Lood consoity table

Load capacity table		
Hinge size (mm)	Load capacity (kg)	Door Width (mm)
102×76×t3	45	Below 850
127×76×t3	50~60	Below 900
127×89×t3	50~60	Below 900

112 113