

-
- A detailed close-up of the door's hinge and latch assembly. The dark-stained wood frame is visible, with a silver-colored metal hinge and a matching latch bolt mounted on the door edge. The latch is in the retracted position, allowing the door to be opened.

-
- Technical drawing of a sliding door system, showing side and cross-sectional views with dimensions and labels.
- Side View (Top):**
- Overall width: 361
 - Distance from left edge to start of track: 145
 - Distance from left edge to end of track: 137
 - Distance from start of track to end of track: 377
 - Track width: 16
 - Track depth: 22
 - Labels: フック (Hook), 引戸枠 (Sliding Door Frame), ソフトクローザー (Soft Closer), スライダー 開始位置 (Slider Start Position), スライダー 全閉位置 (Slider Fully Closed Position)
- Side View (Bottom):**
- Distance from left edge to start of track: 280
 - Track width: 24
 - Track depth: 21
 - Labels: 2-φ12穴 フック取付用 (2-φ12 hole for hook attachment) (付属道具にて穴あけ) (Hole drilling with accessory tool)
- Cross-section A-A (Bottom):**
- Labels: フック (Hook), 引戸枠 (Sliding Door Frame), ソフトクローザー (Soft Closer)
 - Dimensions: φ12 (hole diameter), 21 (track depth), 13 (hook offset)
- Dimensions:**
- 145
 - 361
 - 137
 - 377
 - 16
 - 22
 - 280
 - 24
 - 21
 - φ12
 - 13