Sliding Door Parts



### Clear Cut Hook Lock

This hook lock for indoor sliding doors is good to prevent the door from accidentally being locked. It's impossible to operate the lock unless the door is hitting the trigger part and close perfectly. The product is universal as it can be configured with a standard lever or UD lever with a bigger grip so that everybody can use it easily. UD lever also uses blue and orange indicators, which is easier for anyone to recognize. The cylinder type uses a dimple key that provides 100 combinations, and there are 2 master keys available to generate 126 different child keys combinations. (Please contact us for further details.)

The lock is available in 4 different functions.
The escutcheon is available in round and square types.
The thumb turn is available in standard thumb turn type, standard lever type, and UD lever type.
Available in 6 different colors to guarantee a perfect harmony with the different series of sliding doors.

 $\begin{array}{c} \mathsf{Material:} \langle \mathsf{Rose} \rangle \mathsf{Aluminium} \\ \langle \mathsf{Lever} \rangle \mathsf{ZDC} \end{array}$ 

 $\langle Lock \ Case, \ Strike \rangle \ Stainless, \ Steel \ Door \ Thickness: 30~40mm$ 

Strike Installation Range: Up-Down ± 5mm, Depth 3.5mm

Screw included:

⟨Rose⟩

M4 Flat head machine screw(D6) 2pcs

(Refer to the Rose fixing screw / Spindle specification table)  $\langle {\rm Lock~case} \rangle$ 

 $3.5 \times 20$  Flat head tapping screw(D7) 2pcs  $\langle Strike \rangle$ 

 $3.5 \times 20$  Flat head tapping screw(D7) 2pcs



Round Rectangle type type

Adjustable Strike (Top Lock)



(Indicator lock)

Top Lock BS38

The hook lock strikes out from above. Back set is 38 mm.



Round Rectangle type type Adjustable Strike (Bottom Lock)



Bottom Lock BS51

The hook lock strikes out from the bottom. Back set is 51 mm.



Top Lock BS51

The hook lock strikes out from above. Back set is 51 mm.



Dead Bolt Lock BS51

The hook lock strikes out from above. At the same time, the dead bolt protrudes. Back set is 51 mm.

### ${\bf Rose\ fixing\ screw\ /\ Spindle\ specification\ table}$

Indicator, Privaci lock					
Door thickn	ess (mm)	30~34	35~39	40	
Rose fixing	Standard, Lever type	M4	M4×25		
screw	UD Lever type		$M4 \times 30$		
Spindle		L27	L32	L37.5	

Cyllinder lock					
Door thickn	ess (mm)	30~35	36~39	40	
Rose fixing	Standard, Lever type	M4×	16	M4×25	
screw	UD Lever type		M4×30		
Spindle leng	gth (only spindle)	L21(17.8)	L27	(23.8)	

Two sides Thumb-turn					
Door thickn	ess (mm)	30~34	35~39	40	
Rose fixing	Standard, Lever type	M4×10	M4×16	M4×20	
screw UD Lever type		M4 × 25	M4	× 30	
Spindle		L27	L32	L37.5	






Indicator lock (Outdoor side)



Standard type (Indoor side)




Round Type



Square Type



### Finish/Color



Strike digging drawing

Lock case digging drawing

### Product No. List

Troduc	t NO. LIST													
1) L	ock Case Type	2	Rose Type	3		ks F	unction	4	Finish Type	(5)	Door	Locks	6	Remarks
		Ļ			Inside	Ļ	Outside	Ļ			Thickness	Function		
		$\vdash$		$\vdash$				_						
<del>                                     </del>	Lock BS51					2	Privacy lock	SG	Satin Gold	04	30~34	Privacy lock, Indicator lock,		
<del>                                     </del>	Lock BS38			S	Standard	3	Indicator lock	SW	Satin Silver	59	35~39	Double-sided		
	tom Lock BS51					S	Standard	PG		40	40	thumb turn	Key	No. etc.
ND51R Dea	d Bolt Lock BS51							CR	Chrome Plating	05	30~35			
※Round type	faceplate							TS	Silver Painting	69	36~39	Cylinder lock		
								ТВ	Black Painting	40	40			
NT51S Top	Lock BS51													
NT38S Top	Lock BS38			_										
NU51S Bot	tom Lock BS51			s	Standard	5	Cylinder lock	SG	Satin Gold					
ND51S Dea	d Bolt Lock BS51			L	Otarraara	6	Master key	SW	Satin Silver					
<b>※</b> Rectangle	type faceplate							TS	Silver Painting					
								ТВ	Black Painting					
		R	Round											
						2	Privacy lock	SG	Satin Gold					
				R L	R Lever	3	Indicator lock	SW	Satin Silver					
						R	Master key	PG	Gloss Gold					
						•	•	CR	Chrome Plating					
								TS	Silver Painting					
										ı				
										-				
						5	Cylinder lock	SG	Satin Gold					
				R	Lever	6	Master key	SW	Satin Silver					
						3	Indicator lock	TS	Silver Painting					
						5	Cylinder lock			ı				
				U	UD Lever	6	Master key							
						U	UD Lever							
					l	_	00 2010.							
						2	Privacy lock	SG	Satin Gold					
						3	Indicator lock	SW	Satin Silver					
		s	Square	s	Standard	5	Cylinder lock	ТВ	Black Painting					
						6	Master key							
						s	Standard							
				_			•							

### Example on How to Write a Product Number when Ordering

	1	2	3	4	5	6
Picture A	NT38R	R	S3	SW	04	
Picture B	NT51R	S	S3	ТВ	04	
Picture C	NU51R	R	S2	SW	04	
Picture D	ND51R	S	S6	ТВ	05	65

- X Cylinder lock comes with 2 keys.
- When specifying the key number, enter the key number in the remarks column.
  The finishing color of the strike plate and faceplate is hairline.

Picture C

Picture D

- \* Master key with master key specifications is sold separately.

Lock Case · Adjustable Strike					
Product N	Product No.				
BS38	BS51	Product Name			
NT38R	NT51R	Top Lock Case (Round type faceplate)			
NT38S	NT51S	Top Lock Case (Rectangle type faceplate)			
_	NU51R	Bottom Lock Case (Round type faceplate)			
_	NU51S	Bottom Lock Case (Rectangle type faceplate)			
_	ND51R	Dead Bolt Lock Case (Round type faceplate)			
_	ND51S	Dead Bolt Lock Case (Rectangle type faceplate)			
224-580	same	Adjustable Strike, Top Lock (Round type faceplate)			
900-022	same	Adjustable Strike, Top Lock (Rectangle type faceplate)			
_	224-589	Adjustable Strike, Bottom Lock (Round type faceplate)			
_	224-590	Adjustable Strike, Bottom Lock (Rectangle type faceplate)			

Spare Key					
Product No.					
BS38	BS51	Product Name			
224-581	same	Spare key (No.000)			
224-582	same	Spare key (No.B000)			
224-583	same	Spare key (No.D000)			





TS Hook Lock











TS Hook Lock is a well-design product winning the Good Design Award. It combines a hook lock and a puller in one unit to be attached to an indoor sliding door. The lock-unlock operation can be done easily by sliding the

knob up and down (see fig. Detailed photo 1). It has a streamlined design and a vast surface with some textured parts to highlight a modern minimalist style. On cylinder type, a dimple key with 100 combinations is used to ensure safety. The strike plate is available with or without a trigger, and there are 6 different colors to complement any sliding door color.

Material: (Pull) ZDC

(Lock Case, Strike) Stainless, Steel

Door Thickness: 28~36mm

Strike Installation Range: Up-Down ± 5mm, Depth 3.5mm

Lock				
lo.	Key			
With trigger	Specification	Finish/Color		
224-701T	Privacy lock	Gloss Pearl Chrome		
224-702T		Black Gold		
224-703T		Satin Silver		
224-704T		Black Silver		
224-705T		Matte Black Painting		
224-706T		Chrome Plating		
224-711T	Indicator lock	Gloss Pearl Chrome		
224-712T		Black Gold		
224-713T		Satin Silver		
224-714T		Black Silver		
224-715T		Matte Black Painting		
224-718T		Chrome Plating		
224-721T	Cylinder lock	Gloss Pearl Chrome		
224-722T	<b>%</b> 1	Black Gold		
224-723T		Satin Silver		
224-724T		Black Silver		
224-716T		Matte Black Painting		
224-719T		Chrome Plating		
224-725T	Cylinder lock	Gloss Pearl Chrome		
224-726T	<b>%1·%</b> 2	Black Gold		
224-727T		Satin Silver		
224-728T		Black Silver		
224-717T		Matte Black Painting		
224-720T		Chrome Plating		
224-748T	Lock Case (Round	d type faceplate)		
224-749T	Lock Case (Recta	ngle type faceplate)		
224-580	Adjustable Strike (Round type faceplate)			
	Adjustable Strike	(Rectangle type faceplate)		
	With trigger 224-701T 224-702T 224-703T 224-704T 224-705T 224-706T 224-711T 224-712T 224-713T 224-714T 224-715T 224-721T 224-723T 224-724T 224-725T 224-725T 224-726T 224-727T 224-749T	With trigger Specification  224-701T Privacy lock  224-702T 224-703T 224-704T 224-705T 224-706T 224-711T Indicator lock  224-712T 224-713T 224-714T 224-715T 224-718T 224-721T Cylinder lock 224-723T 224-724T 224-725T Cylinder lock 224-726T 224-726T 224-727T 224-728T 224-728T 224-720T 224-748T Lock Case (Round Lock Case (Recta Adjustable Strike)		

Half indicator. (It only show red color when it locked.)

Spare key

%1 With 2 keys.

224-750 224-750

※2 This cylinder doesn't protrude.

(Only for 33~36mm door thickness.)

- \* The strike plate and faceplate is also available in rectangle type.
- \* The finishing color of the strike plate and faceplate is hairline.

Screw included:

 $\langle Pull \rangle$ 

M4 × 25 Flat head machine screw(D7) 2pcs

(Lock Case)

3.5 × 20 Flat head tapping screw(D7) 2pcs (Strike)

3.5 × 20 Flat head tapping screw(D7) 2pcs





TS Hook Lock






Outdoor side





TS Hook Lock + Adjustable Strike



Strike digging drawing

Pull-Lock Case digging drawing



Detailed photo 1

### With trigger

When the sliding door is open, the hook doesn't protrude. The trigger retracts into the case when the sliding door is closed.



# 30~39mm

### **NS Automatic Hook Lock**

By adding up a magnet, this product not only can prevent the door from not closing perfectly or bouncing back. But it can also automatically lock the door by dropping the hook once the door is pulled to close entirely by the magnet force. Pull the puller to lift the hook, and the door

will become moveable. The product without a lock is also an option for your sliding door.

Material: \(\rightarrow\text{Pull}\rightarrow\text{Resin}\)

(Lock Case, Strike) Stainless, Steel

Door Thickness: DT33\_29.5~34.5mm, DT36\_34.6~39.0mm Strike Installation Range: Up-Down ± 4mm, Depth 4mm

NS Automatic Hook Lock					
Product No	).	Key			
DT33	DT36	Specification	Finish/Color		
224-621	224-624	Passage lock	Chrome Plating		
224-622	224-625		Gold Painting		
224-623	224-626		Silver Painting		
224-631	224-634	Privacy lock	Chrome Plating		
224-632	224-635		Gold Painting		
224-633	224-636		Silver Painting		
224-641	224-644	Indicator lock	Chrome Plating		
224-642	224-645		Gold Painting		
224-643	224-646		Silver Painting		
224-651	224-654	Puller	Chrome Plating		
224-652	224-655		Gold Painting		
224-653	224-656		Silver Painting		

※ □: Enter R for the front Round type or S for the Rectangle type.

- \* The price is for one inside and one outside set.
- X The finish of the front of the lock case and the strike is barrel polishing.

Screw included:

⟨Pull⟩ M3 × 30 Flat head machine screw 2pcs

⟨Lock Case⟩ 4×20 Flat head tapping screw 2pcs

⟨Strike⟩ 4×20 Flat head tapping screw 2pcs



NS Automatic Hook Lock (Indicator lock)





Round type

Locked

Indoor side


Unlocked

Locked


Outdoor side


Unlocked

Square type



Silver Painting





**Chrome Plating** 

**Gold Painting** 

# 30~46mm

### **CL Automatic Hook Lock**

Not only provides the automatic-locking mechanism and other extensive practical benefits, but this lock is also designed exclusively to meet the demand for a good product, functionally and aesthetically. This product uses metal as the material, offering a solid and deluxe

appearance, and the screws are also fixed in a concealed position, creating a

seamless-looking product.

 $Material: \langle Pull \rangle ZDC$ 

⟨Lock Case, Strike⟩Stainless, Steel

Door Thickness:30~46mm

Strike Installation Range: Up-Down ± 4mm, Depth 4mm

CL Automatic Hook Lock (Door Thickness:30~32mm)					
Product No.	Key Specification	Finish/Color			
224-679□	Passage Lock	Chrome Plating			
224-680□		Satin Silver			
224-681		Black Painting			
224-661	Privacy lock	Chrome Plating			
224-662		Satin Silver			
224-663		Black Painting			
224-664	Indicator lock	Chrome Plating			
224-665□		Satin Silver			
224-666□		Black Painting			

CL Automatic Hook Lock (Door Thickness:33~36mm)					
Product No.	Key Specification	Finish/Color			
224-682	Passage Lock	Chrome Plating			
224-683		Satin Silver			
224-684		Black Painting			
224-667	Privacy lock	Chrome Plating			
224-668		Satin Silver			
224-669□		Black Painting			
224-670□	Indicator lock	Chrome Plating			
224-671		Satin Silver			
224-672		Black Painting			

CL Automatic Hook Lock (Door Thickness:37~46mm)					
Product No.	Key Specification	Finish/Color			
224-685□	Passage Lock	Chrome Plating			
224-686		Satin Silver			
224-687□		Black Painting			
224-673	Privacy lock	Chrome Plating			
224-674		Satin Silver			
224-675□		Black Painting			
224-676	Indicator lock	Chrome Plating			
224-677□		Satin Silver			
224-678		Black Painting			

- $\mbox{\%}$   $\square$ : Enter R for the front Round type or S for the Rectangle type.
- X The price is for one inside and one outside set.
- X The finish of the front of the lock case and the strike is barrel polishing.

Screw included:

50

⟨Pull⟩ M3×10, 15, 18 Flat head machine screw 2pcs (Depends on the door thickness.)

 $\langle Lock \ Case \rangle \ 4 \times 20 \ Flat \ head \ tapping \ screw \ 2pcs$  $\langle Strike \rangle \ 4 \times 20 \ Flat \ head \ tapping \ screw \ 2pcs$ 



type type

Adjustable Strike



CL Automatic Hook Lock (Front Round type)












Indicator lock


Chrome Plating


Satin Silver

Black Painting









### Top Hung Soft Closer Set

Made to be installed on an indoor sliding door, this top-hung damper will slowly pull the door from ±70 mm before it closes. Thus, it can reduce the unpleasant noise of the door hitting the frame. The door will close completely without any gap regardless of the strength or speed adjusted during the installation. This product has passed the 200,000 times operation test and comes with an adjustable roller, and wheels with bearing for optimal long-term performance. Not only offering excellent technical function, but this soft closer is also fully recessed to embraces a stylish architectural appearance. This top hung soft closer can be attached to both ends of the door. X1 **%1** Please contact us for further details.

Material: (Main unit, Hook) Stainless ⟨4 Wheels Adjuster⟩Resin (Sliding Door Rail) Aluminum (Guide Pin) Stainless, Resin Load Capacity: 30kg(294N)

Installation Range: Up-Down ± 3mm, Left-Right ± 2mm Finish/Color: \(\lambda\) Main unit, Hook\(\rangle\) Raw Material

4 Wheels Adjuster Amber · White ⟨Sliding Door Rail⟩Silver (Guide Pin) Raw Material

Top Hung Soft Closer Set

Product No.	Finish/Color	Rail Length(mm)
312-031	Amber	1,820
312-032		2,730
312-033		3,640
312-031W	White	1,820
312-032W		2,730
312-033W		3,640
Sat contante		

Top Hung Soft Closer 1pcs, Hook 1pcs

4 Wheels Adjuster 2pcs, Sliding Door Rail 1pcs Anti-Shake Guide Pin 1pcs

Screw included:

⟨Hook⟩

3×16 Flat head tapping screw 2pcs ⟨4 Wheels Adjuster⟩ ¾ Including Soft Closer

3.5 × 12 Flat head tapping screw 2pcs

3.5 × 20 Pan head tapping screw 4pcs

⟨Sliding Door Rail⟩

 $3.5 \times 45$  Flat head tapping screw

(The number depends on the rail length.)

(Anti-Shake Guide Pin)

Wall

52

3.5 × 25 Flat head tapping screw 2pcs










## Top Hung Soft Closer


Top Hung Soft Closer			
Product No.	Finish/Color		
312-037	Amber		
312-037W	White		

Set contents:

Top Hung Soft Closer 1pcs Hook 1pcs



4 Wheels Adjuster



Drawing for Installation

## 4 Wheels Adjuster OK

This product has passed the 200,000 times operation test and uses wheels with bearing for smooth performance. In addition, the lower part can be detached and initially installed to the sliding door with one touch.

Material: Resin. Steel Load Capacity: 30kg(294N) Installation Range: Up-Down ± 3mm, Left-Right ± 2mm

4 Wheels Adjuster	
Product No.	Finish/Color
320-021	Amber
320-021W	White

※ 1pc price. Screw included:

3.5 × 12 Flat head tapping screw 1pcs 3.5 × 20 Pan head tapping screw 2pcs

### **Sliding Door Rail** (without hole for the hook)

Material: Aluminum

Load Capacity: 30kg(294N)

Sliding Door Rail		
Product No.	Length(mm)	Finish/Color
310-512	1,820	Silver
310-522	2,730	
310-532	3,640	
0 1 1	1.	

Screw included:

3.5 × 45 Flat head tapping screw

(The number depends on the rail length.)

## Anti-Shake Guide Pin

Material: Stainless, Resin

27. 8

1.2

47. 5

16 | 15 | 8

39

Amber

White


(11.9)

This pin helps the door running in the track, prevents it from swinging and shaking during opening or closing. When it collides with the door, the cylinder will spin, and the door will operate smoothly. Additionally, as it is concealed by the door, it doesn't interfere with the architectural appearance and causes no dangers for the user.

Load Capacity: 30kg(294N) Anti-Shake Guide Pin Product No. Finish/Color 320-084 Raw Material Screw included:

3.5 × 25 Flat head tapping screw 2pcs





## 4 Wheels Adjuster · Rail set

	•	
4 Wheels Adjuster · Rail set		
Product No.	Finish/Color	Rail Length(mm)
312-034	Amber	1,820
312-035		2,730
312-036		3,640
312-034W	White	1,820
312-035W		2,730
312-036W		3,640
Set contents:		

4 Wheels Adjuster 2pcs, Sliding Door Rail 1pcs, Anti-Shake Guide Pin 1pcs



53

Cabinet Parts · Handrail

## 60kg OK

### **Sliding Door Soft Closer**

This external type of soft closer can be installed on existing sliding doors. This door damper will catch closing doors  $\pm 50$  mm before the thud and then softly and silently close them. Thus, it reduces the unpleasant noise of the door

hitting the frame and prevents the door from bouncing back. The door will close perfectly without any gap regardless

of the strength or speed adjusted during installation. Compared to conventional products, this soft closer has twice better durability (passed 500,000 times operation tests).

It is also possible to modify this product to a concealed type.  $\mbox{\% 1}$   $\mbox{\% 1}$  Please contact us for further details.

Material: Stainless · Resin Load Capacity: 60kg (588N)

Load Capacity: 60kg(588

Finish:

(Stainless) Hairline · Painting

⟨Resin⟩Material coloring

Sliding Door Soft Closer			
Product No.	Door Weight	Finish/Color	
312-061	30kg	Gold Painting	
312-062	(294N)	Silver Painting	
312-063		Hairline	
312-064		<b>Brown Painting</b>	
312-065	60kg	Gold Painting	
312-066	(588N)	Silver Painting	
312-067		Hairline	
312-068		<b>Brown Painting</b>	
Screw included:			


Screw included:

 $\langle \mathsf{Main}\;\mathsf{unit} \rangle$ 


 $3.5 \times 40$  Flat head tapping screw 2pcs  $\langle \text{Trigger} \rangle$ 

3.5 × 25 Binding head tapping screw 2pcs






Soft Closer Main unit



Trigger



Drawing for Installation














This is a door damper for an indoor bottom-running sliding door. It will slowly pull the sliding door from about 80mm before the end, and then it will close slowly and quietly. The door will close completely without any gap regardless of the strength adjusted during the installation. As this product is a concealed type, it will not disintegrate the architectural appearance. In addition, this soft closer

has also passed 200,000 times operation tests which guarantee long-term use.









57





### KT Adjustable Roller


Using this device, adjusting the sliding door position to maintain a smooth operation is possible as, over time, the door will slightly change due to weather and friction.

Material: Resin, Steel Load Capacity: 30kg(294N) Installation Range: Upper\_Left-Right ± 2mm Lower\_Up-Down ± 3mm, Left-Right ± 2mm Appropriate Rail: Upper\_Lintel Rail, Lower\_T Rail


KT Adjustable Roller			
Product No.	Specification	Finish/Color	
301-332	Upper side	Amber	
301-342	Lower side		

※ 1 pc price. Screw included:

4 × 30 Flat head tapping screw 1pcs



Upper side



Lower side



17



Upper side


Material: Aluminum Finish/Color: Amber

Lintel Rail		
Product No.	Specification	Length (mm)
310-312A	Single Rail	1,820
310-312B		2,730
310-312C		3,640
310-412A	Double Rails	1,820
310-412B		2,730
310-412C		3,640


Screw included: 3.5 × 12 Flat head tapping screw (The number depends on the rail length.)



Single Rail Double Rails



Single Rail












This rail is used together with the lower KT Adjusting Roller. As the height of the rail is only 3 mm, this product is barrier-free.

Material: Aluminum Load Capacity: 30kg(294N)

T Floor Rail			
Product No	0.		Length
Amber	Silver	Specification	(mm)
310-361A	310-364A	Single Rail	1,820
310-361B	310-364B		2,730
310-361C	310-364C		3,640
310-362A	310-365A	Double Rails	1,820
310-362B	310-365B		2,730
310-362C	310-365C		3,640
310-363A	310-366A	Triple Rails	1,820
310-363B	310-366B		2,730
310-363C	310-366C		3,640
Screw incl	uded:		

2.7 × 16 Flat head wood screw (The number depends on the rail length.)




Triple Rails


Double Rails

Double Rails

Single Rail

Single Rail









59







Outset Sliding Door Parts With this set, you can easily replace a hinged door

Load Capacity: 30kg(294N)

Outset Sliding Door Parts

with a sliding door.

Outset Shallig Door Farts			
	Upper Rail	Lower Rail	Lower Rail
Product No.	(mm)	(mm)	Color
330-001	1,388	1,392	Amber
330-002	1,570	1,574	
330-003	1,628	1,632	
330-001S	1,388	1,392	Silver
330-002S	1,570	1,574	
330-003S	1,628	1,632	
Sat contents			

Set contents:

Upper Rail 1pcs, Lower Rail 1 pcs

KT Adjusting Roller Door (For lower side) 2pcs

Door Side Guide 2pcs Upper Stopper 2pcs

Lower Stopper 2pcs



## Upper Rail (Outset)

Material: Aluminium Load Capacity: 30kg(294N)

Upper Rail (Outset)			
Product No.	Length(mm)	Finish/Color	
330-051	1,388	White	
330-052	1,570		
330-053	1,628		
Screw included:			

 $3.5 \times 30$  Flat head tapping screw

(The number depends on the rail length.)





### Lower Rail (T Floor Rail)

Material: Aluminium Load Capacity: 30kg(294N)

Lower Rail (T Floor Rail)

Product No.		
Amber	Silver	Length(mm)
330-054	330-057	1,392
330-055	330-058	1,574
330-056	330-059	1,632
Scrow included:		

Screw included:

2.7 × 16 Flat head wood screw (The number depends on the rail length.)






### Material: Resin, Steel Load Capacity: 30kg(294N) Installation Range: Up-Down ± 3mm, Left-Right ± 2mm

KT Adjustable	Roller (Lower side)
Product No.	Finish/Color
301-342-2	Amber


**X** 2pcs price.


Screw included:


4 × 30 Flat head tapping screw 2pcs



















10. 5







Material: Resin

Door Side Guide	
Product No.	Finish/Color
330-060	White
※ 2pcs price.	
Screw included:	

4 × 25 Flat head tapping screw 6pcs



Upper Stopper Product No. Finish/Color 330-061 White **X** 2pcs price.

Screw included: M4 × 10 Flat head machine screw 4pcs




# **Outset Lower Stopper**




Product No.	Finish/Color
330-064	Black
※ 2pcs price.	
Screw included:	

4 × 30 Flat head tapping screw 6pcs







### Strike Plate (for Outset Sliding Door Fitting)

This strike plate is suitable to be used together with the Outset Sliding Door Fittings set. The design is simple, so it doesn't interfere with the architectural appearance.

Material: Stainless, Resin

Installation Range:Left-Right ± 4mm

Front-Back 5.5~7.5mm

Finish/Color: (Cover) White

⟨Bracket⟩Barrel Polishing


Outset Sliding Door Hook Lock Strike

	Strike hole	
Product No.	width(mm)	Spesification
330-005	8.8 × 43	
330-006	$11.8 \times 43$	
330-007	$11.8 \times 33$	Trigger
Screw include	d:	

⟨Base⟩

4 × 50 Truss head tapping screw 3pcs (Plate)

3.5 × 16 Flat head tapping screw 2pcs





# (for Outset Sliding Door Fitting)

This reinforced type strike plate is suitable to be used together with the Outset Sliding Door Fittings set. It is using natural wood, designed in sharp and sturdy looks.

Material: Stainless, Natural wood Installation Range: Left-Right ± 4mm

Front-Back 5.5~7.5mm

Finish/Color: (Cover) White ⟨Bracket⟩ Hairline

OS Sliding Door Wood Strike

**Wooden Strike Plate** 

	Strike hole
Product No.	width(mm)
330-010	16×42
Screw included:	

⟨Front⟩

M5 × 10 Flat head machine screw 2pcs

⟨Cover⟩

4.5 × 20 Flat head tapping screw 2pcs


⟨Base⟩

4 × 50 Truss head tapping screw 5pcs













## High rigidity Strike Plate (for Outset Sliding Door Fitting)

Strike Plate for with increased rigidity. The design is square and color is whiter.

Material: Stainless, Resin

Installation Range: Left-Right ± 4mm Front-Back 6.0~7.5mm

Finish/Color: (Cover) White (Bracket) Barrel Polishing

High rigidity Ctriles Diete

High rigidity Strike Plate	
	Strike hole
Product No.	width(mm)
330-015	12×33
Screw included:	

⟨Base⟩

4 × 50 Truss head tapping screw 4pcs ⟨Plate⟩

 $3.5 \times 16$  Flat head tapping screw 2pcs 4 × 10 Flat P head tapping screw 2pcs

## **Outset Upper Stopper**



Door stopper installed to the wall for outset sliding door use.

Material: Steel, Resin

Outset Upper Stopper Product No. Finish/Color 330-065 Black

\* 1pc price. Screw included:

5 × 50 Pan head tapping screw 3pcs





### **Outset Lower Stopper**

The stopper installed on the floor for the outset sliding door use.

Material: Resin

Outset Lower Sto	pper
Product No.	Finish/Color
330-063	Silver
330-064	Black
※ 2pcs price.	
Screw included:	

 $4 \times 30$  Flat head tapping screw 6pcs



### **Magnet Catcher**



This product is effective in making sure the sliding door stays still and not shaking. It is also good to prevent the sliding doors from bouncing back and reduce the thud of the door hitting the frame.

Material: Resin, Steel, Magnet Load Capacity: 10~35kg(98~343N) Door Thickness: More than 28mm


Magnet Catcher	
Product No.	Finish/Color
230-022	Amber
Screw included:	

3×16 Flat head tapping screw 1pcs



Frame side

Frame side Door side











F2 Adjuster Guide

This rail is used together with the upper rail of a sliding door with lower roller.


Material: Resin Load Capacity: 30kg(294N) Installation Range:Left-Right ± 2mm

F2 Adjuster Guide	
Product No.	Finish/Color
305-012	Amber
* 1pc price.	

% Tpc price.
Screw included:

 $4 \times 45$  Flat head tapping screw 1pcs





## Upper Rail








Material: Aluminium Load Capacity:30kg(294N) Finish/Color: Amber

Upper Rail		
Product No.	Specification	Length(mm)
310-012	One side	1,820
310-022		2,730
310-032		3,640
310-042	Both side	1,820
310-052		2,730
310-062		3,640
0 . 1 .	1.	

Screw included:

3.5 × 25 Flat head tapping screw (The number depends on the rail length.)









(N)

(D)



(C)








(W)



Brown

(B)




## **Door Stopper Cap**

The cap which made of elastomer Resin with good cushioning and durability. We provide with a lot of color variations.

### Material: Resin

Door Stopper	Cap		
	Installation		
Product No.	diameter (mm)	Finish/C	olor
251-001	φ8	Birch	K
251-002		Natural	Ν
251-003		Cherry	С
251-004		Brown	В
251-005		Dark	D
251-009		White	W
251-010		Peach	Υ
251-011	$\phi$ 10	Birch	K
251-012		Natural	Ν
251-013		Cherry	С
251-014		Brown	В
251-015		Dark	D
251-019		White	W
251-020		Peach	Υ
251-021	φ13 ※1	Birch	K
251-022		Natural	Ν
251-023		Cherry	С
251-024		Brown	В
251-025		Dark	D
251-029		White	W
251-030		Peach	Υ
\*/1 / 10 I	1 11 JULY 11 11 11 11 11 11 11 11 11 11 11 11 11		

 $\times 1$   $\phi$  13 color is slightly different.







### Bar Handle

A puller handle for indoor sliding doors. The long bar with Φ30 mm diameter design provides an easier grip when opening a door and prevents your hand from slipping. This is a benefit to the children, the elderly, and those with physical disabilities. This product is available in 5 natural warm wood colors that will go well with any sliding door color.

Material: (Bar) Natural Wood ⟨Rose⟩ADC Door Thickness:27~32mm

Bar Handle		
Product No.	Set content	Finish/Color
863-101LP	Bar Handle	Pale
863-101LD	+ Pull	Dark
863-101WA		White
863-101LL		Rusk
863-101LM		Mocha
863-102LP	Bar Handle	Pale
863-102LD	+ Bar Handle	Dark
863-102WA		White
863-102LL		Rusk
863-102LM		Mocha
Scrow include	۷.	

Dark

M5 × 16 Flat head machine screw 2pcs











White







Both sides bar handle specification



Digging process drawing







Cross section A-A





## Big Handle

A Φ25mm diameter bar puller for indoor sliding doors. It has a complimentary design, combining a wooden bar and stainless steel bracket nicely. This product is aesthetic and usable to the greatest extent as it provides easier gripping for everyone.

Material: (Handle) Stainless, Natural Wood

⟨Bracket⟩ZDC ⟨Cover⟩Resin

Door Thickness: 28~33mm, 34~38mm

Product	DT	Handle		
No.	(mm)	Material	Finish	Color
861-325S	34~38	Stainless	Hairline	Raw material
861-325K		Natural wood	<b>Urethane Painting</b>	Dark
861-325C		Natural wood	<b>Urethane Painting</b>	Middle
861-325F		Natural wood	<b>Urethane Painting</b>	Light
862-325S	28~33	Stainless	Hairline	Raw material
862-325K		Natural wood	<b>Urethane Painting</b>	Dark
862-325C		Natural wood	<b>Urethane Painting</b>	Middle
862-325F		Natural wood	<b>Urethane Painting</b>	Light

 $M6 \times 60$  or  $M6 \times 55$  Pan head machine screw 2pcs

M6 3 types nuts 2pcs M6 Flat washer 2pcs

M6 Spring lock washer 2pcs

Bracket finish: (Bracket) Satin Silver (Cover) Nickel Plating + Clear Coating

\* There is also one side specification. Please contact us for more information.



### Resin Pull Round & Rectangle

This plastic flush pull for an interior sliding door is made of lightweight plastic. It is available in 2 different designs, round and rectangle edges, to suit your room style. The finishing color is also available in 2 beautiful colors to maintain the solid metal look.

Material: Resin


Door Thickness:27~34mm

Resin Pull Round & Rectangle			
Product No.			
Round	Square	Finish/Color	
222-563	222-583	Pearl Chrome	
222-523	222-543	Gold	


※ Price for two pieces as one set.

Screw included:

M4 × 25 Flat head machine screw(D6) 2pcs



Round shape



Square shape












This one-touch flush pull is effortless to install on an interior sliding door. Instead of using screws, it uses an adhesive for the installation. So not only it's functional to your door, but it also gives a beautiful and seamless accent to it.

Material: Resin Door Thickness: 28~34mm

Resin Pull Rectangle One Touch		
Product No.	Finish/Color	
222-598	Pearl Chrome	
222-599	Gold	

\* Price for two pieces as one set.







Pearl Chrome



Pearl Chrome







Pearl Chrome









### Resin One Touch Pull Rectangle

This is a one-touch flush pull made of plastic for an interior sliding door. This product doesn't use screws but an adhesive for an effortless installation and a seamless appearance. The design and the color available are created to match any room and door color. It also creates a perfect match if you use the TS Automatic Hook Lock.

Material: Resin Door Thickness: 28~36mm

Resin One Touch Pull Rectangle		
Product No.	Finish/Color	
222-600	Black Silver	
222-601	Black Gold	
222-602	Mad Black Painting	








Black Silver

Black Gold

Mad Black Painting









### Round & Rectangle Pull

This flush pull for an interior sliding door is made of metal. It is available in 2 different designs, round and rectangle edges, to suit the style of your room. The finishing color is also available in 6 beautiful colors that will easily complement your door color.

Material: ZDC


Door Thickness: 27~34mm


Round & Rectangle Pull Product No. Round Square Finish/Color 224-812 224-912 Gloss Gold 224-813 224-913 Satin Gold 224-814 224-914 Gold Painting Chrome Plating 224-815 224-915 224-816 224-916 Satin Silver 224-817 224-917 Silver Painting

※ Price for two pieces as one set.

Screw included:

M4 × 25 Flat head machine screw(D6) 2pcs









Satin Gold







Gloss Gold



Gold Painting









Satin Gold

Silver Painting





**Gold Painting** 








## Metal One Touch Pull Round & Rectangle

This metal one-touch flush pull is effortless to install on an interior sliding door. Instead of using screws, it uses an adhesive to create a seamless appearance. The design and finishing color are also available in 2 different types to suit any door color.

Material:ZDC

Door Thickness: More than 30mm

Metal One Touch Pull Round & Rectangle				
Product No.				
Round	Square	Finish/Color		
222-671-1	222-677-1	Gloss Gold		
222-672-1	222-678-1	Satin Gold		
222-673-1	222-679-1	Gold Painting		
222-674-1	222-680-1	Chrome Plating		
222-675-1	222-681-1	Satin Silver		
222-676-1	222-682-1	Silver Painting		
222-684-1	222-683-1	Matte Black Painting		
\*/ 1 ·				



Above digging specification can be applied to both round and rectangle shape.



### TK One Touch Flush Pull

This one touch flush pull for an interior sliding door consists


of 2 parts combined which create a stylish design. It has a seamless appearance as it doesn't use any screw for installation. To install, simply apply adhesive and fix it on the door. The length of this product is available in two types, 140 mm and 290 mm.

Material: (End)ZDC **(Bar)** Aluminium

TK (	One	Touch	Flush	Pull	

	Length	Finish/Color	
Product No.	(mm)	End	Bar
224-614	140	Chrome Plating	Alumite Silver
224-614SW		Hairline	Stain Alumite
224-614WH		White Painting	White Painting
224-614BK		Black Painting	Black Painting
224-629	290	Chrome Plating	Alumite Silver
224-629SW		Hairline	Stain Alumite
224-629WH		White Painting	White Painting
224-629BK		Black Painting	Black Painting
₩ 1nc nrice			

% 1pc price.










### **ND Flush Pull**

This flush pull for an interior sliding door has round edges to create a sense of fluid design. It also has a seamless appearance as it doesn't use any screw for installation. To install, simply apply adhesive and fix it on the door.

### Material:ZDC

ND Flush Pull	
Product No.	Finish/Color
224-615	Satin Gold
224-616	Satin Silver
※ 1pc price.	







Satin Gold Satin Silver



Satin Silver



Paint Silver

Satin Silver

Mirror Silver

Paint Black

Flush Edge Pull

The edge pull is intended for the pocket door edge, but this one is also applicable to folding doors and underfloor storage. The product allows the finger grip to retract from the door by pushing the upper part. The appearance is flush mount, and the mounting screws are invisible.

Material:ZDC

Door Thickness: More than 27mm

	i9	
	Product No.	Finish/Color
	220-306	Paint Silver
)	220-307	Mirror Silver
	220-308	Satin Silver
	220309	Paint Black

Finish/Color

Paint Silver


Mirror Silver

Satin Silver

Paint Black

Screw included:

3×12 Flat head tapping screw 2pcs



Flush Edge Pull 72 Product No.


220-301

220-302

220-303

220304

Screw included:




15 (Digging 16)




Paint Silver Mirror Silver



Paint Black













### **Heavy Duty Hung Door**

A set of top-hung track and rollers for indoor sliding doors allows doors weighing up to 100 kg to glide smoothly. This heavy-duty top-hung roller also has passed 500,000 operation tests to ensure the door will operate at its optimum for years to come.

Material: 〈Roller〉Resin, Steel

(Hung Door Rail) Aluminum ⟨Upper Stopper⟩Resin

⟨Floor Guide⟩Resin

Load Capacity: 100kg(980N)

Finish/Color: (Roller) White

(Hung Door Rail)Silver ⟨Upper Stopper⟩White ⟨Floor Guide⟩White

Heavy Duty Hung Door

Product No.	Length of the rail (mm)
320-026	1,820
320-027	2,730
320-028	3,640

Parts included:

Roller 2pcs, Hung Door Rail 1pcs

Upper Stopper 2pcs, Floor Guide 1pcs Screw included:


 $\langle Roller \rangle$ 

 $4 \times 40$  Oval head tapping screw 16pcs (Hung Door Rail)

4 × 45 Flat head tapping screw (The number depends on the rail length.)

〈Floor Guide〉

 $4 \times 30$  Flat head tapping screw 3pcs






Heavy Duty Hung Door







Upper Stopper


Floor Guide





Heavy Duty Hung Door





Floor Guide